

## SANIFOG sanitizing atomizer

Pneumatic atomizer composed of:



- tank in stainless steel
- level indicator
- 2 atomizing adjustable nozzles
- sanitizing regulation valve
- valve for emptying / washing
- safety valve calibrated at 8 bar
- air pressure regulator



The **Sanifog** device transforms the sanitizing liquid into a dry fog of very small particles (15/20  $\mu\text{m}$ ) with high kinetic energy.

Thanks to this technology, the sanitizer saturates the spaces reaching any interstices of the environment, ensuring the sanitization of each surface even those that normally an operator cannot reach with traditional methods.

If used with suitable products it can guarantee the reduction of the microbial and viral load in shops, homes, offices, clinics, public places, commercial establishments, animal farms, etc ...

To operate the appliance, it is necessary to have a compressed air line or to have a portable compressor.



### IMPORTANT

Always check the compatibility of the sanitizer with anatomical materials. Always obtain the safety data sheet for liquids that comply with the indications of the WHO or your own state.



Questo prodotto ricade sotto alcune Direttive comunitarie, pertanto è marcato CE ed ha la "Dichiarazione CE di conformità" nel manuale di istruzioni allegato al prodotto. MADE IN ITALY - PED 2014/68/UE

### Features

Model	NBZ10XF	NBZ25XF
Material	Stainless steel AISI 316	Stainless steel AISI 304
Supply	Pneumatic (compressed air line required)	Pneumatic (compressed air line required)
Tank capacity	10 l	24 l
Maximum quantity of liquid that can be inserted	9.5 l	19 l
dimensions	24 cm x 24 cm H=80 cm	29 cm x 36 cm H=102 cm
Recommended pressure for sanitization	1 – 6 bar	1 – 6 bar
Indicative air consumption (at 3 bar)	160 l/min	160 l/min
Indicative consumption of sanitizer (at 3 bar)	4.84 l/h	4.84 l/h
Coverage at 3 bar (calculated for 6 ml / m <sup>3</sup> )	13.5 m <sup>3</sup> /min	13.5 m <sup>3</sup> /min
Max pressure	8 bar	8 bar
Weight (without liquid)	8.5 kg	11 kg